

Additional Data/Spec Sheet

Dowty Washers | Bonded Seal Self-Centering | Metric Thread | Carbon Steel | Buna Rubber Nitrile Seal

TECHNICAL FEATURES:

- Carbon Steel AISI 1008-1010
- Seal: NBR 85 +/- 5 Sh A
- Surface Treatment: Zinc Plate (Cr3)
- Working Temperature: -30°C to +100°C

Metric Adaptor Bonded seals Steel Dowty Washers				DIMENSIONS mm		
Fluidco Part nr	DICSA Part nr	R1 Metric	Working Pressure (Bar)	L	L1	L2
W-DW-M06	T32006	M6x1	650	1	6.7	10
W-DW-M08	T32008	M8x1	750	1	8.7	13
W-DW-M10	T32010	M10x1	810	1.5	10.7	16
W-DW-M12	T32012	M12x1.5	750	1.5	12.7	18
W-DW-M14	T32014	M14x1.5	900	1.5	14.7	22
W-DW-M16	T32016	M16x1.5	840	1.5	16.7	24
W-DW-M18	T32018	M18x1.5	760	1.5	18.7	26
W-DW-M20	T32020	M20x1.5	690	1.5	20.7	28
W-DW-M22	T32022	M22x1.5	660	2	22.7	30
W-DW-M24	T32024	M24x1.5	630	2	24.7	32
W-DW-M30	T32030	M30x2	500	2	31	39
W-DW-M36	T32036	M36x2	500	2	36.7	46

